


Standard and Athletic Plastisol Colors - Hover over swatches for corresponding Pantone numbers

Lemon Yellow	Chrome Yellow	Golden Yellow	Orange	Flag Red
M,P,U	M, P, U	M, P, U	M, P, U	P
Scarlet Red	Brite Red	Cardinal Red	Maroon	Cool Pink
M, P, U	M, P, U	M, P, U	M, P, U	P
Deep Purple	Navy	Light Navy	Royal Blue	Mono Blue
M, P, U	P, U	M, P, U	M, P, U	M, P, U
University Blue	Brite Blue	Peacock Blue	Aqua Marine	Lime Green
Р	M, P, U	M, U	M, P, U	M, P, U
Brite Green	Kelly Green	Chrome Green	Sienna Brown	Khaki
M, P, U	M, P, U	M, P, U	M, P, U	M, P, U
Cream	Vegas Gold	Light Grey	Dark Grey	Grey
U	P	M, P, U	M, P, U	P, U

Mixopake



Fluorescent - Hover over swatches for corresponding Pantone numbers

Orbit Yellow	Inferno Orange	Aurora Pink	Solar Blue	Traffic Green
M, U, O	M	M, P, U, O	M, O	M, U, O
		Golden Yellow O	Flame Orange O	Neon Magenta O

A GUIDE TO UNION INK TEXTILE INK SERIES

Maxopake Plastisol (PADE) is the highest opacity ink offered by Union Ink. A limited variety of colors are available in bleed-resistant formulations for printing on cotton/polyester blends.


Mixopake Plastisol (MIXE) is a versatile, easy-to-print high opacity ink intended for simulating Pantone® colors on colored garments.

Polyester (ATHP) series of colors are formulated for the high opacity and bleed resistance even on substrates prone to bleed.

Ultrasoft Plastisol (PLUE) ink is a versatile medium opacity ink and is excellent for both direct printing and transfer printing.

GLOBAL COMPLIANCE

Union Ink[™] is certified to **ZDHC Conformance Level 3** with **ECO PASSPORT by OEKO-TEX**.* To learn more about compliance standards, please contact your Avient Specialty Inks distributor.



For more information about Union Ink colors, visit unionink.com.



* Union Ink ECO PASSPORT certification number: Union Ink 2.10 - 22.0.01715

www.avient.com



Copyright © 2024, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.